

Hydraulic Earth Drills - Towable

- Powerful, reliable, safe
- Forward and reverse auger rotation
- Accepts 36" or 42" auger lengths



COMPLETE LINE OF ONE-MAN EARTH DRILLS, AUGERS AND MINI-TRENCHERS















POWER...VERSATILITY...DEPENDABILITY

ittle Beaver's towable, hydraulic earth drill certainly has all of that...and more. When we designed the HYD-TBIIH, we weren't interested in developing an ordinary, "me too" machine. Our goal was to design a towable, hydraulic earth drill that was clearly superior to any competitive offering currently on the market. And that's exactly what we did.



Pneumatic wheels let you easily move the HYD-TBIIH without damaging turf. The machine is incredibly well balanced, requiring less than 20 pounds of force to pivot to the digging position.



The towable design saves valuable truck or trailer space. Simply install the standard, removable tow bar, attach to your 2" ball, and connect the safety chains.

Hydraulic Earth Drills - Towable

MORE POWERFUL

We started with an 11 HP Honda engine. Then, we added a hydraulic system that's second to none. This powerful combo generates up to 262 foot pounds of torque, letting you easily drill holes up to 16" in diameter.

MORE VERSATILE

The HYD-TBIIH features convenient forward and reverse auger rotation and a two-position handle that permits drilling right next to buildings or other structures. An infinitely variable 20 degree auger tilt allows vertical drilling in uneven terrain while our removable "no tools" tow hitch permits easy highway transport.

MORE DEPENDABLE

The HYD-TBIIH is built to last with welded steel plate and tube construction for extra long life. By combining an inlet suction strainer with a 10 micron return filter, the hydraulic system is kept clean of contaminants. And the entire machine is backed by a one year, limited warranty.



Forward/reverse hydraulic levers and an on/off switch are conveniently located on the two-position handle.



An auger lock makes it easy to maneuver the HYD-TB11H around the job site.



A large, 6.5 gallon hydraulic reservoir features a convenient sight gauge and a 10 micron return filter.







The two-position handle rotates 180 degrees, allowing you to drill right next to buildings, walls, or other obstructions. An infinitely variable 20° auger tilt provides vertical drilling in uneven terrain.

C I F I C A T I O N S	Engine	
	Brand / model	Honda GX340 OHV
	Horsepower	l l hp
	Oil alert system	Std.
	Hydraulics	
	Forward / reverse	Std.
	Maximum auger speed	I4I rpm
	Maximum auger torque	262 ft. lbs.
	Maximum flow	6 gpm
	Maximum pressure	2500 psi
	Reservoir capacity	6.5 gallons
	Return filter	10 micron
	Inlet suction strainer	Std.
	Sight level gauge	Std.
	Other Features	
	Construction	Welded steel plate & tube
Γ	Handle	Two-position
	Auger tilt	20 degrees each direction
1H	Auger vertical lock	Std.
	Auger transport lock	Std.
	Towing	
<u> </u>	Removable tow bar	Std.
<u> </u>	SMV sign	Std.
-	Ball hitch	2″
	Tires	5.7-8 highway rated
	Dimensions	
	Overall length	106″
	Length with handle folded	93″
	Height	43″
	Width	34″
	Shipping weight (dry)	575#
	Warranty	One year



P.O. Box 840 • Livingston TX 77351 Toll Free: 800-227-7515 • Phone: 936-327-3121 • Fax: 936-327-4025 www.littlebeaver.com • email: sales@littlebeaver.com

Distributed by: