

Top Lock



The Top-Lock Slat provides an economical and attractive way to enhance any chain link fence.

Pexco is the largest manufacturer of Top-Lock Slats, which are marketed under the PDS® brand name. With over 30 years of experience extruding these innovative, proprietary products, you are assured of the highest standards in quality—from the raw materials used in manufacturing to the finished product in your fence. This design utilizes a top-locking mechanism located near the top of the slats to ensure a clean, straight edge, further enhancing its appearance.

Design

Top-Locking Slats are flat and tubular in shape, with circular, notched-out holes located near the top of the slat.

Standard Heights

4, 5, 6, 7, 8, 10 & 12 feet. Special heights available upon request.

Slat Length

2" shorter than the overall height of fence.

Flexible, Top-Locking Channel

10 feet provided in each bag.

Wind Load and Privacy Factor

Approximately 75%.

Colors*



* Exact representation of slat colors in printing is difficult. Please refer to actual color samples for final matching.



PDS® is a registered trademark of Pexco.

Top Lock Product Specifications



Slat Type	Slat Width	Mesh Size	Wire Gauge	Slats Per Bag	Approx. Coverage Per Box
Top Lock 2"	1 3/32"	2"	8, 9 or 11	82	10 linear feet
Top Lock 2 1/4"	1 1/4"	2 1/4" or 2 3/8"	11 1/2" or 12 1/2"	78	10 linear feet
Top Lock 1 3/4"	7/8"	1 3/4"	8, 9 or 11	97	10 linear feet
	7/8"	2"	6	97	10 linear feet

Materials

The Top Lock product is extruded from High Density Polyethylene (HDPE), color pigments and ultra violet (UV) inhibitors, specifically designed to retard the harmful effects of the sun and lengthen the life of the product.

Durability

Pexco PDS® HDPE Fence Products are resistant to: severe weather conditions, salt water, sand, road dirt, most acids, alcohol, alkaline, ammonia, petroleum distillates, and common environmental pollutants.

Maintenance

Pressure cleaning of surface contaminants is quickly accomplished with plain water.

Wind Load Disclaimer

Pexco will not be responsible for damage due to wind load conditions resulting from insufficient structural support.

Limited Warranty


Top Lock carries a 25-year, pro-rata warranty against breakage under normal conditions. Write Pexco for full warranty information.

HDPE Technical Properties

Property	Value
Melt Index	(.6) A low melt index indicates improved stress and crack resistance.
Density	(.957) Polyethylene ranges anywhere from .914 to .960 in density. A higher density yields maximum stiffness without becoming overly brittle.
Minimum Temp.	(-76° F) Polyethylene stays flexible even at this temperature extreme.
Maximum Temp.	(250° F) Polyethylene does not distort until reaching this temperature.
Tensile Strength	(3,700 psi) Material will not suffer distortion at lesser loads or impacts.


Installation Instructions

Step 1



There is no need to kneel down! Simply insert the slats vertically from top to bottom, keeping the locking holes on top.

Step 2



Thread the flexible locking channel horizontally through the notched holes in the slats.

These holes are elliptical to ensure they always stay open for fast and easy threading.



Pexco Tacoma
Tacoma, WA
800.822.7528

Pexco Athol
Athol, MA
800.755.7528

www.pdsfence.com
www.pexco.com

Contact your local fence professional for more information about our complete line of enhancement products.

