



EXCLUSIVE NEW 9-GAUGE HOG RINGS & PLIERS SYSTEM

EXTRA LEVERAGE & REACH • EASY ACCESS • UNINTERRUPTED FEED • SECURE CONNECTIONS



Clinching mechanism brings ring forward for easy access.



Unique overlap clinch for stronger, more secure connections.

HOG RING PLIERS



Get the job done faster with Malco's commercial-grade Hog Ring Pliers with auto-feed magazine. Quickly install 9-ga. (3.8 mm) collated aluminum rings or our exclusive 9-ga. (3.8 mm) collated steel rings – easily securing 7-ga. (4.5 mm) wire to 9-ga. (3.8 mm) chain link fence.



LONG HANDLES FOR EXTRA LEVERAGE & REACH

HRP5

U.S. Patent Pending

Malco[®]

SL14596

THE EASY-LOAD, AUTO FEED MAGAZINE MAKES A FAST JOB EVEN FASTER.



Catalog Number	Description	Hog Ring Usage	Length in. (cm)	Weight lb. (kg)	Pkg. Qty.
HRP5	Hog Ring Pliers w / Magazine	HRA5 / HRS5	20 (50.8)	2.9 (1.32)	2

- Magazine folds down for safe and easy storage.
- 25-piece loading strips with no sharp points are safe and easy to load.
- Plunger automatically sets up each ring for uninterrupted operation.

HOG RINGS

STRONG AND WEATHER RESISTANT!

Use with HRP5 Hog Ring Pliers with Auto-Feed Magazine.

**THE ONLY
COLLATED
9-GA. STEEL
HOG RINGS
ON THE
MARKET!**



HRS5



HRA5

GALVANIZED STEEL HOG RINGS - HRS5

Class 3 Coating Per ASTM A641
U.S. Patent Pending

ALUMINUM HOG RINGS - HRA5

6061-T94 or 5052-H38 Alloy
U.S. Patent Pending



- 9-gauge (3.8 mm).
- Unique overlap clinch for stronger, more secure connections.
- 25-piece loading strips with no sharp points are safe and easy to load.
- One **500 pack** secures 1000 feet (305 m) of tension wire spaced at 24" (61 cm) intervals.

Catalog Number	For Tools	Material	Crown in. (mm)	Opening in. (mm)	Inside Dia. in. (mm)	Thickness Ga. (mm)	Pkg. Qty.
HRS5	HRP5	Galvanized Steel	1-7/16 (37 mm)	5/8 (16)	7/16 (11 mm)	9 (3.8)	500
HRA5	HRP5	Aluminum Alloy	1-7/16 (37 mm)	5/8 (16)	7/16 (11 mm)	9 (3.8)	500

